



**G-Switch USB-C Specification:**

1. Current rated: 5A on vbus/1.25A on vconn/0.25A on other  
Voltage rating: 24V AC
2. Withstanding voltage: 100V AC/minute
3. Contact resistance: 40mΩ Max
4. Insulation resistance: 100MΩ Min
5. Operating temperature: -40°C ~ +85°C
6. Mating force: 5N~20N
7. Unmating force: 8N~20N
8. Durability cycle: 10,000 cycles

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND			VBUS	CC1	D+	D-	SBU1	VBUS			GND
First			First	Second	Second	Second	Second	First			First

  

B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
GND			VBUS	SBU2	D-	D+	CC2	VBUS			GND
First			First	Second	Second	Second	Second	First			First

此产品符合  
USB协会认证  
规范TID:7346

1	SHELL	STAINLESS STEEL	Au PLATED
2	MID PLATE	STAINLESS STEEL	Ni PLATED
3	HOUSING	HIGH TEMPERATURE PLASTIC	BLACK UL 94 V-0
4	TERMINALS	COPPER ALLOY	Au PLATING ON CONTACT AREA
NO.	PARTS	MATERIAL	REMARKS

SCALE: 1:1	UNIT: mm	Title: Horizontal Type-c 16P Female SMT Sink 0.80 CH=-0.83 L=7.35mm	
SIZE: A4		Molde Code: GT-USB-9014AB	
Unless otherwise General Tolerance:		DRAWN	CHECKED
X.	±0.15	Xia	Chen
X.x	±0.10		
X.xx	±0.05		
X.xxx	±0.02		
X°	±10°		
		APPROVED	DATE
		Chen	2019.02.01

品赞科技®  
 www.dg-switch.com

REV: A0 SHEET: 1/1